



PRODUCT DESCRIPTION

FLOOR AND WALL THIN-SET ADHESIVE

NSA PRO++ is a smooth and creamy thin-set adhesive for installing small to medium format ceramic tiles, vitrified tiles, wall and floor in interior areas.

For improved performance and exterior use, with HI-BOND LATEX ADDITIVE.

Application

Designed for interior floor and wall (Tiles & Stones) Applic

*For exterior installation of tiles/stones with NSA-PRO++, use Latex Additive Admix instead of water.

Advantages

- Hi-bond adhesion strength
- Easy to Apply
- Dual purpose for floor and wall installation with good adhesion and workability
- Extended open time
- Increased flexibility
- High Tack - Will hang tile without slippage
- Improved impact resistance

Suitable Substrates

- Concrete wall and floor areas
- Cement Mortar Beds
- Cement Plaster
- Tile-On-Tile applica
- Brick Masonry
- Cement Terrazzo
- ***When mixed with HI-BOND LATEX ADDITIVE Admixture.

Mixing Ratio: - 20 Kg. Add 5 Ltr. to 6 Ltr. of clean drinking water.

Coverage

Approx. 40-50 sq.ft. per 20kg. bag with (6mm * 6mm) Notch trowel for a bed thickness of 3mm

Note: - The coverage will vary depending on surface undulations & size of tiles / stone.

Packaging: - 20 Kg.

Colour: - Grey

Technical Details :



Parameters	Appearance	Pot Life	Open Time	Working Temp.	Bed Thickness	Tensile Adhesion (28 days)	Shear Adhesion (28 days)	Grouting
Specifications	Grey Powder Type - 1	> 50 mins.	> 30 mins.	-20°C to +80°C	3mm to 10mm	1.00 Mpa	1.00 Mpa	After 8 hrs on walls & 24 hrs on floor

